


Anhydrous Ammonia

Towards High Quality Products & Services

MPA



SPECIFICATION OF ANHYDROUS AMMONIA

Properties		Specification
Ammonia (NH ₃)	min	99.6 %
Residue content	max	0.4 %

** Typical analysis does not constitute a specification*

Packing

TBA

Storage

- ✚ Store in a well-ventilated, dry, cool and secure area.
- ✚ Store in closed carbon steel or stainless steel tanks, which equipped with safety relief valves and vacuum breaker
- ✚ There should be no source of ignition. All electrical equipment should be explosion-proof in the storage areas.

Application

- ✚ Used for production of ammonium and nitrate salts in fertilizer industry
- ✚ Used for production of liquid fertilizer solutions which consists of ammonia, ammonium nitrate, urea and aqua ammonia

Contact Us : mpa.sales@malaysianphosphate.com

The information contained herein is a representation of the average properties of product tested on composite samples and should not be considered a guaranteed specification. Depending on the shipment and sample analyses it may fall outside of the above typical values. In addition, multiple handling, transportation, or improper/extended storage may also affect the tested analysis. User are advised to do your own testing when using and we shall not be responsible for any liability, loss or damage that may occur from any reliance for use based upon the above information. © Copyright 2016. Version 2016/1

MALAYSIAN PHOSPHATE ADDITIVES (Sarawak) SDN BHD

609, Block F, Phileo Damansara 1, No. 9, Jln 16/11, Off Jln Damansara,
46350 Petaling Jaya, Selangor, MALAYSIA

Website: www.malaysianphosphate.com

Phone: 03 – 7958 7329 Fax: 03 – 7958 6329