



SPECIFICATION OF COAL TAR

Properties		Specification
Density (20°C)		1.13 ~ 1.22 g/cm ³
Moisture	max	4.0 %
Ash content	max	0.13 %
Viscosity (E80)	max	4.2
Toluene insoluble (none water basis)	max	9.0 %
Naphthalene content (none water basis)	min	7.0 %

** Typical analysis does not constitute a specification*

Packing

- ✚ Delivery through cargo ship

Storage

- ✚ Store in dry cool areas away from rain, moisture and sunlight in properly sealed packaging.
- ✚ Store far from detrimental / poisonous matter to avoid any cross contamination.

Application

- ✚ Used to manufacture paints, synthetic dyes and photographic materials.
- ✚ Used for making electrodes for the aluminium and steel industries.
- ✚ Incorporated into some parking-lot sealcoat products, which are used to protect and beautify the underlying pavement

Contact Us : mpa.sales@malaysianphosphate.com

The information contained herein is a representation of the average properties of product tested on composite samples and should not be considered a guaranteed specification. Depending on the shipment and sample analyses it may fall outside of the above typical values. In addition, multiple handling, transportation, or improper/extended storage may also affect the tested analysis. User are advised to do your own testing when using and we shall not be responsible for any liability, loss or damage that may occur from any reliance for use based upon the above information. © Copyright 2016. Version 2016/1