


Phosphogypsum

Towards High Quality Products & Services

MPA



SPECIFICATION OF PHOSPHOGYPSUM

Properties		Specification
CaSO ₄ .2H ₂ O	min	90.0 %
SiO ₂		1.5 ~ 5.0 %
P ₂ O ₅	max	1.0 %

* Typical analysis does not constitute a specification

Packing

- ✚ Bulk deliveries of 20 MT in general cargo lorry
- ✚ 25 kg PP woven and 1 MT bulk bags

Storage

- ✚ Store in dry cool areas away from rain, moisture and sunlight in properly sealed packaging.
- ✚ Store far from detrimental / poisonous matter to avoid any cross contamination.

Application

- ✚ Used in cement manufacture and in construction material such as building blocks, gypsum powder, plaster board, road pavements and etc.
- ✚ Used as soil conditioner or filler for fertilizer as it to improve the soil texture

Contact Us : mpa.sales@malaysianphosphate.com

The information contained herein is a representation of the average properties of product tested on composite samples and should not be considered a guaranteed specification. Depending on the shipment and sample analyses it may fall outside of the above typical values. In addition, multiple handling, transportation, or improper/extended storage may also affect the tested analysis. User are advised to do your own testing when using and we shall not be responsible for any liability, loss or damage that may occur from any reliance for use based upon the above information. © Copyright 2016. Version 2016/1

MALAYSIAN PHOSPHATE ADDITIVES (Sarawak) SDN BHD

609, Block F, Phileo Damansara 1, No. 9, Jln 16/11, Off Jln Damansara,
46350 Petaling Jaya, Selangor, MALAYSIA

Website: www.malaysianphosphate.com

Phone: 03 – 7958 7329 Fax: 03 – 7958 6329